

ONYX 7322

Turbine Oil Additive Package

DESCRIPTION

ONYX 7322 is an ashless additive package intended for use in high performance turbine oils. It provides excellent rust and oxidation control, and filterability. These features contribute to longer fluid life and reduced system maintenance.

PERFORMANCE

ONYX 7322 meets the performance requirements of following specifications.

DIN 51515-1
General Electric GEK 32568, GEK 107395, GEK 46506
Siemens TLV 9013 04
Alstom HTGD 90 117
Solar Turbines ES9-224
ISO 8068
DIN 51524-1

RECOMMENDED DOSAGE

1.2% Wt.

KEY PERFORMANCE BENIFITS

- Excellent oxidation resistance
- Rust and corrosion protection
- Water Separation
- Excellent filterability
- Resistance to sludge formation

PHYSICAL / CHEMICAL CHARACTERISTICS

Properties	Specifications	Typical Value	Test Methods
Kinematic Viscosity@ 40°C, cSt	Report	76	ASTM D445
Density @ 15.5°C, g/ml	Report	0.943	ASTM D1298
Flash Point, °C	Report	160	ASTM D92

GENERAL HANDLING INSTRUCTIONS:

Neoprene or nitrile rubber gloves and safety goggles should be worn for handling. Material safety data sheet should be consulted for specific information and for information on health and safety.

Temperature Recommendations:

Unloading:	Temperature	
Pumping temperature	40°C	104°F
Maximum temperature	50°C	122°F
Storage:		
Maximum temperature for long term storage	40°C	104°F
Blending:		
Max. Base oil temperature for mechanical or in-line mixing	50°C	122°F

NOTE

If you require further information, please contact your regional Onyx representative.